

SUZHOU SEAPEAK CO., LTD.

PE Layflat Hose

<u>PE layflat hose</u> is also widely used in irrigation. It is characterized by low temperature resistance. At the same time, it is easy to use in large quantities due to its light weight.



Constructions of PE Layflat Hose

Pe woven layflat hose is constructed of jacket and lining. The jacket is made of high-strength synthetic fibre (quality polyester filament, polypropylene filament and PE filament) and the lining is made of polyethylene.

Features of PE Layflat Hose

Lightweight, pressure resistance, frost resistance, aging resistance, against-erosion, against acid and alkali, no percolation, easy-usage.

Applications of PE Layflat Hose

Agriculture irrigation, mine industry, municipal water transportation and infrastructure construction etc.

sales@irrigationhoses.com



SUZHOU SEAPEAK CO., LTD.

Specifications and main technical data of PE Layflat

Hose

| Туре | | | | Adhesive (N/25mm) |
|--|------|------|------|----------------------|
| Standard | 2" | 4.5 | 13.7 | ≥20 |
| | 2.5" | 3.7 | 11 | ≥20 |
| | 3" | 3.2 | 9.8 | ≥20 |
| | 4" | 2.3 | 7 | ≥20 |
| | 6" | 1.3 | 3.8 | ≥20 |
| Reinforced (including light-against type) | 2" | 6.5 | 20 | ≥20 |
| | 2.5" | 6 | 18 | ≥20 |
| | 3" | 6 | 18 | ≥20 |
| | 3.5" | 5 | 15 | ≥20 |
| | 4" | 4 | 12 | ≥20 |
| | 5" | 3 | 10 | ≥20 |
| | 6" | 2.5 | 8 | ≥20 |
| | 7" | 2 | 6 | ≥20 |
| | 8" | 1.5 | 5.5 | ≥20 |
| High-pressure | 2" | 11.7 | 35 | ≥20 |
| | 2.5" | 10 | 32 | ≥20 |
| | 3" | 9 | 29 | ≥20 |
| | Ц" | 8 | 25 | ≥20 |
| | 6" | 6.7 | 20 | ≥20 |

Size: 1"-16" Length: 1-100M

www.irrigationhoses.com